

PLENUM RATED MAXCELL SPECIFICATIONS

MaxCell, is a flexible textile innerduct solution designed to increase conduit capacity by up to 300% and reduce installation time by 50% when compared to standard rigid innerducts. Now, in addition to the Standard and Detectable products for OSP applications, MaxCell is available in a Plenum rated configuration. Plenum rated MaxCell is designed to provide low-friction pathway advantages for inbuilding environments.

- Manufactured in the U.S.
- UL 2024 (OFCR FT-6) Listed Evaluated for installation in other spaces used for environmental air in accordance with the National Electrical Code, ceiling cavity plenums and raised floor plenums in accordance with NFPA 76 and NFPA 90A as well as riser and general purpose applications.
- Low-smoke, zero-halogen rated
- Color differentiated pull tapes are pre-installed within each cell
- Available in 1", 2", 3" and 4" configurations
- Allows for simplified cable installations short runs are installed easily and often by hand
- Allows for easy removal of obsolete cables

| PRODUCT* | PART # |
|--------------------------------|----------------|
| 4" 3-cell Plenum, Black Thread | MXP4003BK#### |
| 3" 3-cell Plenum, Black Thread | MXP3456BK#### |
| 2" 3-cell Plenum, Black Thread | MXP2003BK#### |
| 2" 2-cell Plenum, Black Thread | MXP2002BK#### |
| 2" 1-cell Plenum, Black Thread | MXP2001BK#### |
| 1" 3-cell Plenum, Black Thread | MXPM3303BK#### |
| 1" 2-cell Plenum, Black Thread | MXPM3302BK#### |
| 1" 1-cell Plenum, Black Thread | MXPM3301BK#### |



ORDERING GUIDELINES:

- "####" = Associated standard length for appropriate reel selection
- Standard lengths are: 250ft, 500ft, 1,000ft, 2,650ft, 5,300ft and 10,000ft
- Contact MaxCell customer service regarding custom lengths
- Reel sizes may vary

*The designation of size listed for MaxCell products is indicative of the minimum conduit interior diameter in which that product should be installed.

Plenum rated MaxCell supports the same recommended cable diameters as the Standard and Detectable product lines. See www.maxcell.us or contact customer service for specifications, application assistance and/or recommended capacity consultation.

